Product information

PI 39/17/02/2020

Hypoid Gear Oil (GL4/5) TDL SAE 75W-90



Description

Properties

- fuel economy

Semi-synthetic hypoid gear oil with extremely high performance reserves. Excellent aging stability. Even under the most difficult conditions and during large temperature fluctuations, it ensures flawless functioning of mechanical components. Minimizes wear, enables long oil change intervals, and complete with a high viscosity index.

Areas of application

Specifically developed for use in commercial vehicles. Universal total drive line oil (TDL) for application in shift, auxiliary and differential transmissions without scribed specifications from the unit or vehicle manufacturer.

Application The operating instructions of the vehicle and transmission manufacturers must be followed.

- reduces frictional losses - assures optimum shifting performance

limited-slip differentials. Use according to the pre-

Specifications and approvals:

- increases the lubricating effect

- outstanding viscosity stability

API GL4 • API GL5 • API MT-1

- universal application

LIQUI MOLY also recommends this product for vehicles or assemblies for which the following specifications or original part numbers are required:

DAF • Eaton • MAN M 3343 Typ M • Scania STO 1:0 • ZF TE-ML 02B • ZF TE-ML 08 • ZF TE-ML 16B • ZF TE-ML 17B • ZF TE-ML 19B

Available pack sizes

500 ml Can plastic 1406 D-GB-I-E-P 1 l Can plastic 1407 D-GB-I-E-P

1 l Can plastic 2655

D-PL-H-RO-TR 3945 1 l Canister plastic

D-RUS-UA

3939 4 l Canister plastic D-RUS-UA

20 l Canister plastic 1408 D-GB-I-E-P

60 l Drum sheet metal 4708

D-GB

205 l Drum sheet metal 4709 D-GB

Our information is based on thorough research and may be considered reliable, although not

legally binding.

Technical data

SAE class (gear oils) 75W-90 **SAE J306** Density at 15 °C 0,880 g/cm3 DIN 51757 Viscosity at 40 °C 81.4 mm²/s ASTM D 7042-04 Viscosity at 100 °C 14.0 mm²/s ASTM D 7042-04 Viscosity at -40°C (Brook- <= 150000 mPas

field) ASTM D 2983-09

Viscosity index 178

DIN ISO 2909

Pour point -48 °C

Din ISO 3016

180 °C Flash point

DIN ISO 2592

Color number (ASTM) L3.0

DIN ISO 2049