

EHT

Extra High Temperature Grease



GENERAL DESCRIPTION:

MOLYSLIP EHT GREASE is a non melt bentone based grease containing Molybdenum Disulphide and Graphite. Designed for use in high temperature conditions up to 250°C

PERFORMANCE AND USAGE:

MOLYSLIP EHT GREASE is recommended for applications where the lubricant is exposed to higher temperatures. Even if carbonisation should occur, the high content of molybdenum disulphide and other solid lubricants continue to provide protective lubrication.

EXTRA INFORMATION:

MOLYSLIP EHT GREASE is also recommended for use at normal temperatures where pressures are high and speeds are low and where a lubricant of soft consistency is preferred. Completely resistant to water and steam. It is unaffected by acids and alkalis and by aqueous solutions of most chemicals.

TECHNICAL DATA:

Grease Base	Bentone
Consistency N.L.G.I	No. 1
Solids Content	12 % (MoS ₂ , Graphite and others)
Worked penetration at 25°C	310/340
Drop Point	None
Temperature Range	10°C to 250°C

PACKAGING:

450 g tins boxed in 24's, or 400 g cartridges boxed in 24's
5 kg tins boxed in 4's
12.5 kg and 25 kg kegs and 180 kg barrels

01 May 2009