

Description

Carburettor Housing Cleaner is a special mixture of solvents for fast and thorough removal of grease-type contaminants and deposits on carburettors and injection systems such as housings, throttle valves, injectors and bores.

Properties

- good cleaning action
- rapid cleaning
- cleaning possible without dismantling
- economical
- simple to use

Technical data

Color / appearance	gelb / yellow
Propellant	Propan, Butan / propane, butane
Form	flüssig, aerosol / liquid, aerosol
Base	Lösungsmittelgemisch / mixture of solvents
Flash point	-60 °C
Odor	charakteristisch / characteristic

Areas of application

Used for degreasing and cleaning the inside and outside of carburettors and fuel injection systems.

Application

LIQUI MOLY GmbH

89081 Ulm-Lehr

Jerg-Wieland-Str. 4

Spray all components which are exposed with the air filter removed and with the engine switched off. Spray external components and allow to dry. Repeat cleaning in extreme cases. Start the engine and allow to run at a moderate speed. Do not spray painted components.

For parts which have been repainted, check paint for compatibility and colour changes by testing on a hidden area.

Germany

Available pack sizes

400 ml Can aerosol	3325 D-GB-I-E-P
400 ml Can aerosol	1844 D-NL-F-GR-ARAB
300 ml Can aerosol	2406 I
400 ml Can aerosol	3918 D-RUS-UA

Our information is based on thorough research and may be considered reliable, although not legally binding.

