



Thuban® GL5 EP

Extreme Pressure Automotive Gear Oil

Product Data Sheet

Customer benefits

Reduced maintenance costs

Special dispersant in the “clean gear” technology additive package suspends sludges and carbonaceous deposits in the gear oil, preventing their deposition on gear components and oil seals, thus avoiding the need for premature overhaul due to deposit-induced seal wear or leakage. Outstanding thermal stability minimizes the total amount of deposits that the dispersant has to deal with.

Extended gear equipment life

High performance, sulfur-phosphorus EP additive system provides excellent load carrying capacity to protect gear equipment against surface distress (i.e., spalling, pitting, scoring and wear) under heavily loaded conditions. The special inhibitor system resists corrosion of copper alloys and ferrous metals.

Prolonged oil service life

Highly refined base oil and special inhibitor system provides excellent oxidation stability to resist oil degradation and thickening during long periods of severe high temperature operation.


Applications

- Automotive hypoid gear differentials operating under high speed and/or low speed, high torque conditions where API GL-5 performance gear oils are required or permitted.
- Heavy-duty, non-synchronized manual transmissions where API MT-1 performance gear oils are specified.
- Automotive steering gears where API GL-5 performance gear oils are permitted.

Not recommended for manual transmissions other than as mentioned above except where the manufacturer explicitly allows the use of API GL-5 performance oils.

Product features:

- **Thuban®GL5 EP** is a high performance, multipurpose, thermally stable, EP automotive gear lubricant formulated with “clean gear” technology for applications where API GL-5 and/or API MT-1 performance is required.



Product specifications

THUBAN® GL5 EP		
KEY PROPERTIES		
SAE Grade	80W-90	85W-140
Product Code	510275	510276
Pour Point, °C	-30	-15
Timken OK Load, kg	27	27
Viscosity,		
mm ² /s @ 40°C	140	344
mm ² /s @ 100°C	15.0	25.5
Viscosity Index	108	97

ENVIRONMENT, HEALTH and SAFETY

Information is available on this product in the Material Safety Data Sheet (MSDS) and Customer Safety Guide. Customers are encouraged to review this information, follow precautions and comply with laws and regulations concerning product use and disposal.

To obtain a MSDS for this product, visit: www.caltex.com.

1410

Performance standards

- API GL-5
- API MT-1
- Mack GO-J Approval
- MIL-L-2105D
- MIL-PRF-2105E
- SAE J2360



Thuban® GL5 EP

Service Considerations

Modern automotive and heavy-duty equipment places severe demands on gear oils. Heavier loads, diverse driving conditions, terrain and more aerodynamically designed body shapes have resulted in higher operating temperatures for differentials, transmissions and steering gear units.

At elevated gear oil temperatures, it has been found that many gear oils used in manual transmission and differential applications can allow sludge and hard carbonaceous deposits to form which cause oil seal wear, leading to leakage and premature equipment failure. Consequently, more thermally stable, "clean gear" oils are required to resist oil degradation and deposit formation.

Thuban GL5 EP is a thermally stable, "clean gear" technology gear oil, incorporating additional dispersant chemistry in its additive package to suspend any sludges and carbonaceous deposits which form, and prevent their deposition on oil seals, gears and critical yellow metal components of transmissions. Thuban GL5 EP is recommended for use in outside of warranty applications requiring SAE J2360 or MIL-PRF-2105E performance level automotive gear oil.

For a minority of automotive drive axles of the spiral bevel types API GL-4 performance lubricants are specified. Thuban GL5 EP may be used in such applications as long as there is not a prohibition on the use of API GL-5 performance lubricants due to, for example, the presence of copper alloy materials such as bronze bushes. In all cases the manufacturer's operating instructions should be consulted.

Some European heavy duty drive axles, such as those from Mercedes Benz, MAN and ZF require gear oils that meet specific builder additional requirements in addition to API GL-5. For such applications Chevron offers a range of alternative gear oils that meet the various manufacturer requirements, including Hypoid LD.

API MT-1 designates the type of service that is characteristic of non-synchronized manual transmissions, as commonly used in North American heavy-duty equipment. Lubricants meeting the requirements of API MT-1 provide protection against the combination of thermal degradation, component wear and oil seal deterioration, which is not provided by lubricants that meet the requirements of API GL-5 alone.


Except for the North American heavy-duty manual transmissions for which API MT-1 performance oils are acceptable, and a very small number of other manual transmissions, Thuban GL5 EP is in general not suitable for use as a manual transmission fluid (MTF).

Manual transmission fluids (MTFs) are now generally highly specialized products, and there is significant divergence of OEM requirements and diversity of product types. It is true that many MTFs meet API GL-4, but this is largely incidental, as primarily they are defined by other requirements including but not limited to materials compatibility, synchromesh performance and durability, shift feel properties, and gear wear and pitting protection. API GL-5 and GL-4 class drive axle gear oils are not required to meet these requirements, as their specification requirements and qualification tests are wholly drive axle-based.

Chevron offers a wide range of purpose-designed MTFs for both light and heavy duty applications. These include: Easy Shift, Delo® Synthetic Transmission Fluid, Delo® Trans Fluid ESI, Delo® Manual Transmission Fluid, and Translube LD.

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:
Chevron Lubricants
– Asia Pacific



Thuban® GL5 EP

Service Considerations

Manual transmission fluids (MTFs) are now generally highly specialized products, and there is significant divergence of OEM requirements and diversity of product types. It is true that many MTFs meet API GL-4, but this is largely incidental, as primarily they are defined by other requirements including but not limited to materials compatibility, synchromesh performance and durability, shift feel properties, and gear wear and pitting protection. API GL-5 and GL-4 class drive axle gear oils are not required to meet these requirements, as their specification requirements and qualification tests are wholly drive axle-based.

Chevron offers a wide range of purpose-designed MTFs for both light and heavy duty applications. These include: Easy Shift, Delo® Synthetic Transmission Fluid, Delo® Trans Fluid ESI, Delo® Manual Transmission Fluid, and Translube LD.

This bulletin was prepared in good faith from the best information available at the time of issue. While the values and characteristics are considered representative, some variation, not affecting performance, can be expected. It is the responsibility of the user to ensure that the products are used in the applications for which they are intended.

Produced by:
Chevron Lubricants
– Asia Pacific