



ENDURO 600 SX 10W-40

High Performance Synthetic Engine Oil

industry
INDUSTRIE

farming
FARMING

consumers
PARTICULIERS

mines
MINES

transport
TRANSPORT

marine
MARINE

public works
TRAVAUX PUBLICS

ENDURO 600 SX 10W-40 is a synthetic multigrade Engine Oil, designed to meet the latest specifications of both European and American manufacturers of heavy diesel engines. It provides excellent protection against deposits in turbocharged engines, and improved protection against camshaft wear.

ENDURO 600 SX 10W-40 can be used on modern equipment as well as older equipment which uses diesel with either high or low sulfur levels.

ENDURO 600 SX 10W-40 ensures very good cold flow, even in the presence of biodiesel, and significantly reduces wear. It contains selected base oils and suitable additives to provide very good thermal and oxidation stability, control contamination, and reduce downtime.

Benefits

- Excellent thermal stability and oxidation resistance insuring an excellent protection on a large temperature range.
- Great Shear stability
- Outstanding detergency and dispersing aptitudes allowing soot control, preventing the formation of sludge and piston deposits.

Applications

- Heavy Duty engines manufactured by European, American and Japanese companies for on road and off road applications.
- Trucks and Buses operating long drain intervals and used in severe conditions.
- Off Highway, agricultural and mines equipments.
- Mix fleet (gasoline and diesel) light duty and commercial vehicles.

Specifications

ENDURO 600 SX 10W-40

Meets the following Specifications

API CI-4/CH-4/CG-4/CF-4/CF/SL	✓
ACEA E7/A3/B3/B4	✓
JASO DH-1	✓
Daimler Chrysler MB 228.3	✓
Cummins CES 20078/7/6/2/1	✓
Mack EO-M Plus	✓
Volvo VDS-3	✓
MAN M3275	✓
MTU Type 2	✓
Renault RLD 2	✓
CATERPILLAR ECF-1a/ECF-2	✓

Typical Properties

Test Parameters	ASTM Method	Test Values
Density at 15°C, kg/m ³	ASTM D 4052	872
Viscosity at 40 °C, cSt	ASTM D 445	92.2
Viscosity at 100 °C, cSt	ASTM D 445	14.6
Viscosity Index	ASTM D 2270	165
Falsh Point, °C	ASTM D 92	230
TBN, mg KOH/g	ASTM D 2896	10

Above characteristics are mean values given as information.

They do not constitute a specification.

Health and safety

If used accordance with our recommendations and for the applications for which it is designed, this lubricant poses no particular health risk. In accordance with legal requirements, a safety data sheet is available from your sales advisor. When disposing of used oil, please observe all current regulations and protect the environment. Above characteristics are mean values given as an information. They do not constitute a specification.