

Fleetguard[®]



ES Compleat™

Lifetime Heavy Duty Fully Formulated Antifreeze/Coolant

- Extended service lifetime coolant with service interval at 250.000 km/4.000 hours
- Provides antifreeze and antiboil protection
- Best liner pitting and corrosion protection
- Best aluminum and solder protection
- Compatible with gaskets, elastomers and other non-metallics in the engine
- Optimizes cooling system performance and water pump life
- Contains proprietary scale inhibitors
- Compatible with all other antifreeze/coolants
- Choose from EG, PG & Glycerin formulations
- Available in concentrate, 50/50 and 60/40
- For all diesel, gasoline and natural gas engines

ES Compleat™ is formulated specifically for use in heavy-duty diesel engines. These products contain conventional heavy-duty chemical and organic corrosion inhibitors, which provide enhanced protection for diesel engines from liner pitting and hard water scale deposits. In addition, ES Compleat™ products provide the highest water pump protection available in the marketplace. Fleetguard ES Compleat™ Concentrate mixes readily with clean tap water or, better still, de-mineralised water (50/50 mix), while ES Compleat™ Premix is fully formulated with de-mineralised water and ready to use.



ES Compleat™ is fully compatible with all other antifreeze/coolants and corrosion inhibitor packages. ES Compleat™ Antifreezes are universal products highly recommended for use in all heavy-duty diesel engines, and also for use in automobile and light duty applications. ES Compleat™ is formulated to last till engine rebuilt and can be used until contamination levels are exceeded.

Use ES Compleat™ to provide superior engine protection, extend service intervals...

ES Compleat™ is available in the following part numbers

	EG Concentrate	*EG PreMix	PG Concentrate	*PG PreMix
Bulk	CC2822M	CC2827M	CC2832M	CC2837M
1000 L Container	CC2851M	CC2852M	CC2853M	CC2854M
208 L Drum	CC2821M	CC2826M	CC2831M	CC2836M
20 L Container	CC2749M	CC2750M	CC2753M	CC2754M
5 L Bottle	CC2747M	CC2748M	CC2751M	CC2752M

* All premix part numbers are 50% glycol / 50% water (50/50) unless otherwise noted. When noted, the first number indicates % glycol followed by the % water.

... and to simplify your cooling system maintenance program.

Typical properties	ASTM test no.	EG Conc.	EG Premix 50/50	PG Conc.	PG Premix 50/50
Colour	Visual	Blue	Blue	Blue	Blue
Specific Gravity @15°C	D1122	1.13	1.07	1.05	1.045
pH	D1287	10.5	10.5	10.5	10.5
Reserve Alkalinity (ml)	D1121	10.0	> 5.0	10.0	> 5.0
Freeze point (°C)	D1177	< -14	< -36	< -56	< -32
Boiling point (°C)	D1120	> 174	> 108	> 160	> 105
Water, weight (%)	D1123	4	< 47	4	< 47
Glycol, weight (%)	-----	> 95	> 51	> 95	> 51
Glassware corrosion test	D1384	Pass	Pass	Pass	Pass
Water pump cavitation test	D2809	Pass	Pass	Pass	Pass
Aluminium corrosion test	D4340	Pass	Pass	Pass	Pass
Simulated service test	D2570	Pass	Pass	Pass	Pass
Ash content (%)	D1119	< 5	< 2.5	< 5	< 2.5
Chloride (ppm)	-----	< 25	< 25	< 25	< 25

Frequently asked questions

■ **How do I have to use ES Compleat™ concentrate?**
In Heavy Duty applications it is necessary to maintain an antifreeze/ glycol (EG or PG) concentration of 40 to 60 %, depending on your work environment. A 50/50 mix of good quality water, or demineralised water, and antifreeze is preferred.

■ **Do I also need to apply a 50/50 mix in hot climate conditions?**
Besides offering freeze protection, antifreeze also increases the boiling point of the coolant to avoid boiling on hot surfaces (i.g. cylinder heads) in the cooling system. Antifreeze also supports the suppression of liner pitting and cooling system corrosion.

■ What's the major benefit of using ES Compleat™ Premix products?

ES Compleat™ Premix is an easy and ready-to-use product, eliminating the risk of diluting the system. It contains the appropriate amount of inhibitors and anti-freeze (EG or PG) for your initial cooling system fill and worry-free top-up afterwards.

■ What are the benefits of using ES Compleat™ PG?

Propylene Glycol (PG) has a much lower toxicity than Ethylene Glycol (EG). PG is considered safer for use in the environment primarily because of the lower acute toxicity. PG is not considered a hazardous pollutant. OSHA has not seen the need to set a limit regarding human exposure. These benefits make PG a more user and environmentally friendly product.

Fleetguard's ES Compleat™ EG and PG

Extended Life Coolants meet or exceed the performance requirements of the following:

TMC RP-338 Extended Life ▪ TMC RP-329 (EG) ▪ RP-330 (PG) ▪ ASTM D-4985 (EG) ▪ D-5216 (PG) ▪ ASTM D-6210 (EG) ▪ ASTM-6211 (PG) ▪ CID-A-A-52624 Waukesha® 4-1974D ▪ GM6038M ▪ Cummins® SB 3666132 ▪ Cummins® CES 14603 ▪ Caterpillar® ▪ Detroit Diesel® 7SE298 ▪ John Deere® 8650-5 Case New Holland® Navistar® ▪ Freightliner® 48-22880 ▪ Volvo® ▪ PACCAR® ▪ MACK® 014617004 ▪ EMD M.I. 1784E



Filtration

For more information, visit cumminsfiltration.com

LT15070GB
©2009 Cummins Filtration
Printed in Belgium.