

# MOLYSLIP®

## MBG Moly Bentone Grease



### GENERAL DESCRIPTION:

MOLYSLIP MBG is a Bentone grease with Molybdenum Disulphide. The Bentone base gives great stability at high temperatures, resistance to water and acids, and infusibility. It will not soften under heavy working conditions up to its working temperature limit.

### PERFORMANCE AND USAGE:

All medium and large size plain bearings, large diameter ball and roller bearings running at low speeds. For mechanical equipment, particularly when exposed to severe weather conditions or subjected to extreme loads i.e. cranes - conveyor systems - ore crushers - rolling mills etc.

### EXTRA INFORMATION:

Reduces wear and ensures longer life.

Protects against oxidation and corrosion.

Resistant to water and aqueous solutions of acids and alkalis.

Minimises fretting corrosion.

Prolongs periods between maintenance and routine greasing.

### TECHNICAL DATA:

	Standard Grade
Base	Bentone
Consistency N.G.L.I.	No.2
Worked penetration at 25°C	265-295
Drop Point (I.P.31)	None (infusible)
Water Resistance	Complete
Continuous Working Temperature	-20°C to 200°C
Closed Flash Point of Base Oil	232°C

### PACKAGING:

450g tins boxed in 24's, or 400 g cartridges boxed in 24's

3kg tins boxed in 4's

12.5kg and 25kg kegs and 180kg barrels

01 May 2009