



TEKMA MEGA X 10W-40

Lubricant for Diesel engine

SHPD: « Super High Performance Diesel »

Technosynthese®

TYPE OF USE

All low emissions European, American or Japanese Diesel engines naturally aspirated or Turbocharged, in line with Euro II, Euro III, Euro IV and Euro V fitted with EGR System (Exhaust Gas Re-circulation) or SCR (Selected Catalyst Reduction): Trucks, Bulldozers, Construction machinery, Buses, Farm machinery, stationary engines, boat engines...

Can be used as single lubricant in case of fleet composed of new & old generation engines.

PERFORMANCES

| | |
|--------------|--|
| STANDARDS | ACEA E7 (Replaces E5 and E3) API CI-4 / CH-4 |
| APPROVALS | MACK EO-N, MAN M 3275, MB-Approval 228.3, RVI RLD-2, VOLVO VDS 3 |
| PERFORMANCES | CATERPILLAR ECF-1, Global DHD-1, MTU Type II, SCANIA LDF-2 |

Also recommended for other OEMs such as CUMMINS, DAF, IVECO ...

Lubricant reinforced with synthetic base stock providing, at the same time, outstanding resistance at high temperature, easier flowing at cold temperature and longer lubricant life time.

The API CI-4 performance ensures protection and durability of engines fitted with EGR systems:

- Dispersant and anti-oxidation properties: protection against soot build-up and oil filter plugging.
- Superior Anti-Wear level: bore polishing protection.
- Superior detergent level: piston cleanliness and piston groove deposits control.

The 10W viscosity grade at cold temperature drastically improves wear protection at cranking and provides significant fuel economy in frequent start-ups driving mode.

Anti-corrosion, Anti-rust, Anti-foam.

RECOMMENDATIONS

Drain interval: refer to manufacturers' recommendations, tune to your own use (engine type, service).

Can be mixed with synthetic or mineral oils.

PROPERTIES

| | | |
|----------------------------|------------|--------------------------|
| Viscosity grade | SAE J 300 | 10W-40 |
| Density at 20°C (68°F) | ASTM D1298 | 0.871 |
| Viscosity at 40°C (104°F) | ASTM D445 | 100.6 mm ² /s |
| Viscosity at 100°C (212°F) | ASTM D445 | 15.0 mm ² /s |
| Viscosity index | ASTM D2270 | 156 |
| Flash point | ASTM D92 | 230°C / 446°F |
| Pour point | ASTM D97 | -30°C / - 22°F |
| TBN | ASTM D2896 | 11.5 mg KOH/g |

We retain the right to modify the general characteristics of our products in order to offer to our customers the latest technical development.

Product specifications are not definitive from the order which is subject to our general conditions of sale and warranty. - Made in France

MOTUL - 119 Bd Félix Faure - 93303 AUBERVILLIERS CEDEX - BP 94 - Tel: 33 1 48 11 70 00 - Fax: 33 1 48 33 28 79 - Web Site: www.motul.com

04/15