

RUBIA TIR 7400

15W-40



Very high performance lubricant for diesel engines.

USES

All industrial vehicles

- Developed to answer to the very severe technical constraints of the new low-emission Diesel engines.

All types of services

- Adapted to the most severe servicing conditions: transports; public works...

Environment

- Complies with the the EURO 2 and EURO 3 technologies.

PERFORMANCES

Specifications

ACEA E5
API CI-4 / SL
GLOBAL DHD-1

OEMs approvals

DAIMLER CHRYSLER MB page 228.3
MAN M 3275
CUMMINS 20076/20077/20078
VOLVO VDS-2
MTU TYPE 2
MACK EO-M+
RENAULT TRUCKS RLD

CUSTOMER BENEFITS

Increased drain intervals

- Its very high performance level insures longer drain intervals.

One lubricant for your fleet

- Use the same lubricant for all the diesel engines of your fleet, whatever their make.

Very high technical performances

- Exceptional antiwear and anticorrosion properties.
- Good efficiency against bore polishing.
- Excellent viscosity stability in operation.
- Very high detergency and dispersancy levels (limits oil thickening due to soots).

CHARACTERISTICS

	Units	SAE Grade 15W-40
Volumetric mass at 15°C	kg/m ³	883
Viscosity at 100°C	mm ² /s	14
Viscosity index	-	142
Flash point	°C	235
Pour point	°C	-30
T.B.N	mgKOH/g	13.3

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX

RUBIA TIR 7400 15W-40
January 2004



This lubricant, used in accordance with our recommendations and for the application for which it is intended, does not represent a special hazard. A safety data file conforming to the requirements of current EC legislation is available from you local trade consultant.