

RUBIA XT



Multigrade oil for diesel engine

USES

- For all turbocharged or normally aspirated Diesel engines of vehicles operating in the most severe conditions whatever the seasons.
- Suited for extended drain intervals (up to 30 000km according to manufacturers).

PERFORMANCES

Specifications

ACEA E2
API CF-4/SJ
MIL-L-2104E

OEMS' approvals

MERCEDES BENZ 228.1
MAN 271
VOLVO VDS
CATERPILLAR TO-2
ALLISON C-4
KOMATSU

CUSTOMER BENEFITS

Technical performances

- Multigrade
- Very high viscosity index
- Excellent viscosity stability in operation
- Excellent detergency level
- Very high dispersancy level
- Excellent antiwear and anticorrosion properties
- Very good antioxidant, antirust, antifoaming properties

CHARACTERISTICS

Rubia XT	Units	SAE Grade	
		15W-40	20W-50
Volumetric mass at 15°C	kg/m ³	890	887
Viscosity at 40°C	mm ² /s	105	169
Viscosity at 100°C	mm ² /s	14,2	18,8
Viscosity index	-	135	125
Flash Point	°C	225	212
Pour point	°C	-30	-30

The typical characteristics mentioned represent mean values.

TOTAL LUBRIFIANTS
16, rue de la République
92800 PUTEAUX
1/1

RUBIA XT
June 2004



This lubricant, when used according to our recommendations and for the purpose for which it is intended, presents no particular hazards.
A safety data sheet complying with current EC legislation can be obtained from your local commercial adviser.