



## Wolver Super Light 10W-40

### VERPACKUNG

208 L | 60 L | 20 L | 5 L | 4 L | 1 L

**WOLVER Super Light SAE 10W-40** is an highly alloyed lightrun petrol and diesel engine oil enabling by its additives, selection of grand oils and its viscosity application an energy-saving operation of car diesel engines.

To guarantee the lowest viscosity of the SAE 10W-range as well as simultaneously a low volatilization loss **WOLVER Super Light SAE 10W-40** lightrun engine contains full synthetic components meeeting the demands of high tech.

### SPECIFICATIONS:

SAE 10W-40  
API SN/CF  
ACEA A3/B3, A3/B4  
ILSAC GF-4

### MEETS THE REQUIREMENTS OF:

MB 229.1  
VW 501.01, 502.00, 505.00  
BMW Special

### **Characteristics**

- Extrem wear protection
- Excellent viscosity-temperature behaviour
- High oxydation- and thermo stability
- Minimal frictional loss
- Very high cleaning capability
- Low volatilization loss

### **Effects**

- Very good operating reliability
- Excellent cold starting properties - rapid supply of all points of lubrication
- Optimal high temperature viscosity
- Constant operating properties
- Maximum performance results
- Reduced fuel consumption
- Optimal engine cleanliness
- Low oil consumption

- All-year operation

### **Utilization**

- High-performance and normal four-stroke petrol engines
- with multivalve technology
- with turbo charging
- with catalyst technology
- Passenger car diesel engines
- with turbo charging
- Suction diesel
- CDI- HDI- and TDI-motors
- with CDi-technology
- Direct-injection
- with catalyst technology

### **Disposal**

- **WOLVER Super Light SAE 10W-40** is assigned to category 2 of used oils and thus is free for disposal.

### **Miscibility**

**WOLVER Super Light SAE 10W-40** is fully compatible to comparable lubrications and can be mixed without any doubts. However, it is recommended to take **WOLVER Super Light SAE 10W-40** when refilling.

### **Data table**

PROPERTIES	UNIT	TYPICAL INDICATORS
Kinematic viscosity at 100 °C	mm <sup>2</sup> /s	14.1
Viscosity index	-	159
Pour point	°C	-33
Viscosity CCS at -25 °C	mPa·s	6400
TBN	mgKOH/g	8.2
Flash point	°C	212
Density at 15.6 °C	kg/m <sup>3</sup>	873

1L - Can	4105	4260360941054
4L - Can	4303	4260360940033
20L - Pail	4061	4260360940613
60L - Barrel	4191	4260360941917
208L - Barrel	4031	4260360940316