

MOTO TOWN 4T 20W50



MOTORCYCLE

Lubricants

Description

Refined lubricant oil especially designed for 4-stroke petrol engine motorcycles the greater part of whose activity is developed in an urban environment. Its additives prolong its life in this type of working conditions.

Properties

- Guarantees good lubrication in normal service conditions
- Prevents the formation of lacquers and varnishes thanks to its dispersant additives.
- Its degree of viscosity guarantees perfect performance in warm atmospheres.
- Its detergency ensures the piston is properly cleaned.
- It maintains an adequate pressure and temperature under all service conditions.

Quality Levels

- API SG / JASO MA2

Technical specifications

	UNIT	METHOD	VALUE
SAE GRADE			20W50
Density at 15 °C	g/cm ³	ASTM D 4052	0.888
Viscosity at 100 °C	cSt	ASTM D 445	18
Viscosity at 40 °C	cSt	ASTM D 445	157
Viscosity at -15 °C	cP	ASTM D 5293	9500 max.
Viscosity index	-	ASTM D 2270	126
Flash point, open cup	°C	ASTM D 92	248
Pour point	°C	ASTM D 97	-24
T.B.N.	mg KOH/g	ASTM D 2896	7,4
Bosch Injector Shearing: Viscosity at 100°C after shear	cSt	CEC-L014-93	16.3 min.
Noack Volatility, 1h a 250 °C	% in weight	CEC-L-40-93	6,2
HTHS, Viscosity at 150 °C	cP	CEC-L-36-A-90	3.7 min.

A safety information file is available on request.

repsol.com
+34 901 111 999

Technical data sheet for Lubricants. Revision 2. November 2015.