

★ SYNTHETIC ATF

This is a full synthetic lubricant based on carefully selected very high quality base oils, which meets the requirements of the General Motors Dexron VI specification. Its special composition allows it to be used in all applications, where the older Dexron II and Dexron III fluids are recommended.

★ APPLICATIONS

This high quality ATF can be used in automatic transmissions with torque convertors of passenger cars, as well as in wet clutches and power steering units.

★ PERFORMANCE LEVEL

- Dexron VI
- Mercon LV
- MB 236.1/236.5/236.7/236.8/236.9/236.41
- VAG G-055-025/G-052-162
- Aisin Warner JWS 3309/3324 (WS)
- Allison TES 228/C3/C4
- BMW ETL7045/7045E/8072B/LA2634/Mini Cooper T-IV
- Chrysler Dodge Mopar AS68RC (Type IV)
- Chrysler Dodge Mopar ATF+/+2/+3/+4
- Fiat Type IV
- Ford Mercon WSS-M2C138-CJ/166-H/922-A1/924-A
- GM Dexron IID/IIIE/IIIG/IIIH/TASA
- Honda Acura DW-1/ATF-Z1 (except in CVT)
- Hyundai/Kia SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR
- Hyundai/Kia JWS3314/9683
- Isuzi Besco atf II/III, Nissan Matic C/D/J/K/S
- Jaguar ATF 3403 M115/JLM 20238
- JASO M315-2013 1A/1A-LV/2A
- Mazda ATF DII/M-III/M-V/FZ/F-1/S-1/N-1/3317
- Mitsubishi SK/SP-II/SP-III/SP-IV/AW/J2/J3/ATF PA
- Opel, Porsche ATF 3403-M115/Type IV
- Subaru ATF/ATF 5AT/ATF HP
- Suzuki ATF 3309/3314/3317/2326/2384 K
- Toyota D-II/D-III/T-III/T-IV/WS
- Voith 55.6335
- Volvo 1161540/97340
- ZF 5HP 18FL/19FL/24A/30/4 HP 20, ZF TE-ML 11A/11B



★ FEATURES

Frictional properties : very smooth gear shifting, no vibration.

Anti-wear protection : significantly extended transmission life.

Extended oil life : excellent thermal and oxidation stability

★ CHARACTERISTICS

	unit	average value
Density at 15 °C	kg/l	0.847
Viscosity 40 °C	mm ² /s	30
Viscosity 100 °C	mm ² /s	6.0
Viscosity Index		151
Brookfield viscosity at -40 °C	mPas	12000
Color		RED

★ PACKAGING



12x1L

20L

60L

210L

IBC