

★ SYNTHETIC ATF

This is a full synthetic lubricant based on carefully selected very high quality base oils, specifically developed for the dual clutch transmissions (DCT) of modern passenger cars. It ensures trouble-free operation of these gearboxes.

★ APPLICATIONS

Mainly intended for the DSG (Direct Shift Gearbox) of VAG, this fluid can also be used for other 6-speed DCT transmissions, such as Chrysler Powershift, Ford Powershift, Mitsubishi TC-SST, Volvo Powershift, BMW Drivelogic 7-speed, etc. This product is not intended for VW dry clutch DSG type 0AM,02M,02Q and 02S.

★ PERFORMANCE LEVEL

- BMW: DCTF-1
- BMW: MTF LT-5
- CHRYSLER: 68044345EA
- FERRARI: TF DCT-F3
- FIAT: 9.55550-MZ6
- FORD: WSS-M2C936-A
- MB: 236.21
- MB: 236.25
- MITSUBISHI: DIAMOND QUEEN SSTF-1
- NISSAN: R35 SPECIAL
- PORSCHE: 000.043.20
- PORSCHE: 000.043.207.29
- PORSCHE: 000.043.207.30
- PSA: 9734 S2
- RENAULT: BOT450 EDC 6-Speed
- VOLVO: BOT341 #1161838
- VW: G 052 182
- VW: G 052 513
- VW: G 052 529
- VW: TL 52182



★ FEATURES

Anti-wear protection : significantly extended transmission life.

Frictional properties : very smooth gear shifting, no vibration.

Extended oil life : excellent thermal and oxidation stability

★ CHARACTERISTICS

	unit	average value
Density at 15 °C	kg/l	0.854
Viscosity 40 °C	mm ² /s	34.00
Viscosity 100 °C	mm ² /s	7.00
Viscosity Index		173
Flash Point COC	°C	201
Pour Point	°C	-48

★ PACKAGING



12x1L



20L



60L



210L



IBC