

## REVMAX DIESEL ULTRA 15W/40 CF-4

### PRODUCT DESCRIPTION

Revmax diesel ultra 15W/40 CF-4 is multigrade mineral lubricant for on-road diesel engines, heavy-duty diesel engine oil that provides shear stability under wide variety of severe service conditions. Developed for all diesel engines, turbocharged or not, in severe service conditions in all seasons.

### MARKET APPLICATION

- Designed for use in severe conditions for high speed, four stroke both naturally aspirated, turbo charged diesel engines.
- Mixed fleet diesel engines (high speed, four stroke, naturally aspirated or turbo charged).
- Mixed fleets of both diesel and gasoline engines.

### PERFORMANCE LEVEL

- API CF-4
- MIL 2104E
- ALLISON C-4
- VOLVO VDS, MAN 271, VOLVO VDS, CAT TO-2

### TYPICAL CHARACTERISTICS

Properties	Test Methods	Unit	Typical values
SAE GRADE			15W/40
Kinematic Viscosity @ 40°C	ASTM D445	Cst	110
Kinematic Viscosity @ 100°C	ASTM D445	Cst	14.5
Viscosity Index	ASTM D2270		135
Pour Point	ASTM D97	°C	-30
Flash Point	ASTM D92	°C	230
Specific Gravity @ 15°C	ASTM D1298	Kg/L	0.885

Manufactured by Optimum Lubricants Ltd.  
P.O. Box 49925-00100, Nairobi, Kenya  
ISO 9001:2015 Certified

### BENEFITS

1. High thermal and oxidation stability
2. Excellent lower temperature properties
3. Wear protection and viscosity stability

### HEALTH & SAFETY

#### Handling and storage:

When using, do not eat, drink or smoke.

Avoid prolonged or repeated contact with skin.

Use only in well-ventilated areas.

Wear appropriate personal protective equipment.

Avoid release to the environment.

Use appropriate container to avoid environmental contamination.

Wash contaminated clothing before reuse.

Observe good industrial hygiene practices.

For product usage instructions, please see the product label.

#### Precautions for safe handling:

Keep away from heat and sources of ignition.

Store in a cool, dry place out of direct sunlight.

Keep container tightly closed.

Store in a well-ventilated place.

Store away from incompatible materials.