

Revton Hydraulic Oils

VISCOSITY GRADES

ISO VG 32,46,68,100,220

PERFORMANCE LEVELS

Equivalent to:

1. Vickers 1-286-S, M-2960-S
2. Denison HF-1, HF-2 HF-0

MARKET APPLICATION

Revton range of hydraulic oils are premium quality hydraulic oils suitable for both high and low pressure industrial and mobile hydraulic systems. They have outstanding thermal and oxidative stability in addition to superior hydrolytic stability and filter blockage tendency.

PRODUCT DESCRIPTION

Revton range of hydraulic oils are made from selected mineral oils and blended with additives to impart excellent thermal and oxidative stability as well as corrosion inhibition. They have outstanding anti-wear properties.

TYPICAL CHARACTERISTICS

Revton Hydraulic Oils					
Grade ISO	32	46	68	100	220
Specific Gravity@ 15/15°C	0.87	0.88	0.88	0.89	0.90
Kin.Viscosity@40°C, cst(typical)	32.0	46.0	68.0	100.0	220
Viscosity Index Max	60	99	99	98	98
Antiwear Metal	Zn	Zn	Zn	Zn	Zn

BENEFITS

1. Anti-wear properties
2. Reduces sludge and deposit formation
3. System efficiency and longer life
4. Designed to protect against oxidation

HEALTH & SAFETY

Handling and storage:

When using, do not eat, drink or smoke.

Avoid prolonged or repeated contact with skin.

Use only in well-ventilated areas.

Wear appropriate personal protective equipment.

Avoid release to the environment.

Use appropriate container to avoid environmental contamination.

Wash contaminated clothing before reuse.

Observe good industrial hygiene practices.

For product usage instructions, please see the product label.

Precautions for safe handling:

Keep away from heat and sources of ignition.

Store in a cool, dry place out of direct sunlight.

Keep container tightly closed.

Store in a well-ventilated place.

Store away from incompatible materials.